

15W单组防水式 15W Single Output Waterproof Power

概述

- >单组输出: 功率15W
single output: 15W
- >输入电压: AC170~264V
input voltage range: AC170~264V
- >IP67



常见规格General Specification

132 × 30 × 20mm

性能Specification	型号Model	LPV-15W-12	LPV-15W-24
直流输出电压、电流 DC output		12V 1.1A	24V 0.7A
纹波及噪音 Wave and noise		120mVp-p	150mVp-p
进线稳定度 Inlet stability		± 0.5%	± 0.5%
负载稳定度 Load stability		± 1%	± 0.5%
效率 Efficiency		78%	80%
直流电压可调范围 Adjustable range for DC voltage		12V ± 10%	24V ± 10%
输入电压范围 AC input voltage range		85-364VAC 47-63HZ	
冲击电流 AC Inrush current		冷启动电流 Cold-start current	30A/230V 30A/230V
过载保护 Overload protection		105%~150%切断输出, 自动恢复 105%~150% hiccup mode, auto-recovery	
过电压保护 Over-voltage protection		121%~142% rated output voltage	
启动、上升、保持时间 Setup rise hold up time		800ms 20ms 24ms /230VAC at full load	
耐压性 Withstand voltage		输入输出间: 1.5KvAC 输入与外壳间: 1.5Kv 输出与外壳间: 0.5Kv 一分钟 I/P-O/P: 1.5Kv I/P-FG: 1.5Kv O/P-FG: 0.5Kv 1minute	
隔离电阻 Isolation resistance		输入输出间 输入与外壳间 输出与外壳间: 500VDC/100MΩ I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ	
工作温度 Working temperature		-10°C~+50°C	
安全标准 Safety standards		符合GB4943, UL60950, EN60950 Design refer to GB4943, UL60950, EN60950	
EMC标准 EMC standards		符合GB9254, UL55022 等级B Design refer to GB9254, UL55022, classB	
重量 Weight		0.2kg	

外形尺寸 Overall dimension(mm)

