



MS-120W单组输出小体积电源 MS-120W Single output mini-size power supply

概述 Summary

- > 单组输出: 功率120W
Single output: power 120W
- > 输入电压: 90~132VAC/180~264VAC 由开关切换
Input voltage: 90~132VAC/180~264VAC by switch



常见规格 General Specification

159 × 98 × 38mm

性能 Specification	型号 Model	MS-120-12	MS-120-15	MS-120-24	MS-120-27	MS-120-36	MS-120-48
直流输出电压、电流 DC output voltage, current		12V 0~10A	15V 0~8A	24V 0~5A	27V 0~4.4A	36V 0~3.3A	48V 0~2.5A
纹波及噪音 Wave and noise		100mVp-p	100mVp-p	100mVp-p	100mVp-p	100mVp-p	100mVp-p
进线稳定度 Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
负载稳定度 Load stability		±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
效率 Efficiency		83%	84%	86%	86%	86%	86%
直流电压可调范围 Adjustable range for DC voltage		±10%	±10%	±10%	±10%	±10%	±10%
输入电压范围 Input voltage range		90~132VAC/180~264VAC 由开关切换 254~370VDC 47~63Hz 90~132VAC/180~264VAC by switch 254~370VDC 47~63Hz					
冲击电流 Impact current		冷启动电流 Cold start current 15A/115VAC 30A/230VAC					
过载保护 Overload protection		105%~150%切断输出, 自动恢复 105%~150% cut off the output, automatic recovery					
过电压保护 Over voltage protection							
启动、上升、保持时间 Setup, rise, hold up time		200ms, 50ms, 20ms/230VAC 满负载 at full load					
耐压性 Withstand voltage		输入输出间: 1.5kV 输入与外壳间: 1.5kV 输出与外壳间: 0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute					
隔离电阻 Isolation resistance		输入输出间 输入与外壳间 输出与外壳间: 500VDC/100M Ω I/P-O/P I/P-FG O/P-FG: 500VDC/100M Ω					
工作温度 Working temperature		-10℃ ~ +50℃					
尺寸 Dimension		159×98×38mm					
重量 Weight		0.55kg					
包装 Packing		34×32×24CM/30PCS/16.5kg					

外形尺寸 Overall dimension (mm)

