

NDR-75W单组输出导轨电源 NDR-75W Single output DIN rail power supply

概述 Summary

- > 单组输出: 功率75W
Single output: power 75W
- > 输入电压: 85 ~ 264VAC 120 ~ 370VDC
Input voltage: 85 ~ 264VAC 120 ~ 370VDC



常见规格 General Specification

32*125.2*102 mm

性能 Specification	型号 Model	NDR-75-12	NDR-75-15	NDR-75-24	NDR-75-48
直流输出电压、电流 DC output voltage, current		12V 0~6.3A	15V 0~5A	24V 0~3.2A	48V 0~1.6A
纹波及噪音 Wave and noise		80mVp-p	120mVp-p	120mVp-p	150mVp-p
进线稳定度 Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
负载稳定度 Load stability		±0.5%	±0.5%	±0.5%	±0.5%
效率 Efficiency		85.5%	88%	88%	89%
直流电压可调范围 Adjustable range for DC voltage		±10%	±10%	±10%	±10%
输入电压范围 Input voltage range	85 ~ 264VAC 120 ~ 370VDC 47 ~ 63Hz				
冲击电流 Impact current	冷启动电流 Cold start current 20A/115VAC 40A/230VAC				
过载保护 Overload protection	105% ~ 150%切断输出, 自动恢复 105% ~ 150% cut off the output, automatic recovery				
过电压保护 Over voltage protection	121% ~ 142%关闭输出, 电源重启后可恢复输出 121% ~ 142% shut down O/P voltage, re-power on to recover				
启动、上升、保持时间 Setup, rise, hold up time	1200ms, 60ms, 60ms/230VAC 满负载 at full load				
耐压性 Withstand voltage	输入输出间: 1.5kV 输入与外壳间: 1.5kV 输出与外壳间: 0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute				
隔离电阻 Isolation resistance	输入输出间 输入与外壳间 输出与外壳间: 500VDC/100MΩ I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ				
工作温度 Working temperature	-10°C ~ +50°C				
尺寸 Dimension	32 * 125.2 * 102 mm				
重量 Weight	0.51kg				
包装 Packing	42 × 25 × 24CM				

外形尺寸 Overall dimension(mm)

Terminal Pin No. Assignment (TB1)

Pin No.	Assignment
1	FG Ⓢ
2	AC/N or DC -
3	AC/L or DC +

Terminal Pin No. Assignment (TB2)

Pin No.	Assignment
1,2	DC OUTPUT -V
3,4	DC OUTPUT +V

