



概述 Summary

- > 单组输出: 功率1200W
Single output: power 1200W
- > 输入电压: 100~132VAC/200~264VAC 由开关切换
Input voltage: 100~132VAC/200~264VAC by switch

常见规格 General Specification

291 × 132 × 68mm

性能 Specification	型号 Model	S-1200-12	S-1200-24	S-1200-36	S-1200-48
直流输出电压、电流 DC output voltage, current		12V 0~100A	24V 0~50A	36V 0~33A	48V 0~25A
纹波及噪音 Wave and noise		150mVp-p	180mVp-p	180mVp-p	240mVp-p
进线稳定度 Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
负载稳定度 Load stability		±0.5%	±0.5%	±0.5%	±0.5%
效率 Efficiency		80%	85%	85%	87%
直流电压可调范围 Adjustable range for DC voltage		±10%	±10%	±10%	±10%
输入电压范围 Input voltage range		100~132VAC/200~264VAC 由开关切换 254~370VDC 47~63Hz 100~132VAC/200~264VAC by switch 254~370VDC 47~63Hz			
冲击电流 Impact current		冷启动电流 45A/230VAC Cold start current			
过载保护 Over load protection		105%~135%切断输出, 自动恢复 105%~135% cut off the output, automatic recovery			
启动、上升、保持时间 Setup, rise, hold up time		2000ms, 50ms, 20ms/230VAC 满负载 at full load			
耐压性 Withstand voltage		输入输出间: 1.5kV 输入与外壳间: 1.5kV 输出与外壳间: 0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute			
隔离电阻 Isolation resistance		输入输出间 输入与外壳间 输出与外壳间: 500VDC/100M Ω I/P-O/P I/P-FG O/P-FG: 500VDC/100M Ω			
工作温度 Working temperature		-10℃ ~ +50℃			
尺寸 Dimension		291 × 132 × 68mm			
重量 Weight		2.65kg			
包装 Packing		37.5 × 31 × 25.5CM/6PCS/16kg			

外形尺寸 Overall dimension(mm)

