

概述 Summary

- > 单组输出：功率15W
Single output: power 15W
- > 输入电压：90 ~ 132VAC/180 ~ 264VAC 由开关切换
Input voltage: 90 ~ 132VAC/180 ~ 264VAC by switch



常见规格 General Specification

98 × 97 × 35mm

性能 Specification	型号 Model	S-15-5	S-15-12	S-15-15	S-15-24
直流输出电压、电流 DC output voltage, current		5V 0~3A	12V 0~1.3A	15V 0~1A	24V 0~0.7A
纹波及噪音 Wave and noise		50mVp-p	50mVp-p	75mVp-p	100mVp-p
进线稳定度 Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
负载稳定度 Load stability		±1%	±0.5%	±0.5%	±0.5%
效率 Efficiency		65%	68%	70%	72%
直流电压可调范围 Adjustable range for DC voltage		±10%	±10%	±10%	±10%
输入电压范围 Input voltage range		90 ~ 132VAC/180 ~ 264VAC 由开关切换 254 ~ 370VDC 47 ~ 63Hz 90 ~ 132VAC/180 ~ 264VAC by switch 254 ~ 370VDC 47 ~ 63Hz			
冲击电流 Impact current		冷启动电流 Cold start current 15A/115VAC 30A/230VAC			
过载保护 Overload protection		105% ~ 150%切断输出，自动恢复 105% ~ 150% cut off the output, automatic recovery			
过电压保护 Over voltage protection					
启动、上升、保持时间 Setup, rise, hold up time		200ms, 100ms, 30ms/230VAC 满负载 at full load			
耐压性 Withstand voltage		输入输出间：1.5kV 输入与外壳间：1.5kV 输出与外壳间：0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute			
隔离电阻 Isolation resistance		输入输出间 输入与外壳间 输出与外壳间：500VDC/100MΩ I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ			
工作温度 Working temperature		-10°C ~ +50°C			
尺寸 Dimension		98 × 97 × 35mm			
重量 Weight		0.3kg			
包装 Packing		43 × 32.5 × 24CM/60PCS/18kg			

外形尺寸 Overall dimension(mm)

接线位置

- ☒ 端口 1: 直流输出+V
- ☒ 端口 2: 直流输出-V
- ☒ 端口 3: 接地⊖
- ☒ 端口4,5: 交流输入

Terminal Pin No. Assignment

- ☒ Pin 1: DC output+V
- ☒ Pin 2: DC output-V
- ☒ Pin 3: GND ⊖
- ☒ Pin 4,5: AC input

