



291 × 132 × 136mm

概述 Summary

- > 单组输出: 功率 2000w
Single output: power 2000w
- > 输入电压: 200 ~ 264VAC
Input voltage: 200 ~ 264VAC

常见规格 General Specification

性能 Specification	型号 Model	S-2000-24	S-2000-27	S-2000-36	S-2000-48
直流输出电压、电流 DC output voltage, current		24V 0 ~ 83A	27V 0 ~ 74 A	36V 0 ~ 55A	48V 0 ~ 41A
纹波及噪音 Wave and noise		120mVp-p	200mVp-p	200mVp-p	240mVp-p
进线稳定度 Inlet wire stability		± 0.5%	± 0.5%	± 0.5%	± 0.5%
负载稳定度 Load stability		± 0.5%	± 0.5%	± 0.5%	± 0.5%
效率 Efficiency		80%	85%	86%	87%
直流电压可调范围 Adjustable range for DC voltage		± 10%	± 10%	± 10%	± 10%
输入电压范围 Input voltage range		200 ~ 264VAC 200 ~ 264VAC			
冲击电流 Impact current		冷启动电流 Cold start current 45A/230VAC			
过载保护 Overload protection		105% ~ 135%切断输出, 自动恢复 105% ~ 135% cut off the output, automatic recovery			
启动、上升、保持时间 Setup, rise, hold up time		2000ms, 50ms, 20ms/230VAC 满负载 at full load			
耐压性 Withstand voltage		输入输出间: 1.5kV 输入与外壳间: 1.5kV 输出与外壳间: 0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute			
隔离电阻 Isolation resistance		输入输出间 输入与外壳间 输出与外壳间: 500VDC/100MΩ I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ			
工作温度 Working temperature		-10°C ~ +50°C			
尺寸 Dimension		291 × 132 × 136mm			
重量 Weight		5.3kg			
包装 Packing		38 × 37.5 × 21CM/2PCS/11kg			

外形尺寸 Overall dimension(mm)

