

## T-60W三组输出电源 T-60W Triple output power supply



### 概述 Summary

- > 三组输出：功率60W  
Triple output: power 60W
- > 输入电压：85 ~ 264VAC 120 ~ 370VDC  
Input voltage: 85 ~ 264VAC 120 ~ 370VDC

### 常见规格 General Specification

159 × 98 × 38mm

性能 Specification	型号 Model	T-60A			T-60B			T-60C			T-60D		
		CH1主回路	CH2次回路	CH3次回路	CH1主回路	CH2次回路	CH3次回路	CH1主回路	CH2次回路	CH3次回路	CH1主回路	CH2次回路	CH3次回路
直流输出电压、电流 DC output voltage, current		5V 0~5A	12V 0~2.5A	-5V 0~0.5A	5V 0~5A	12V 0~2.5A	-12V 0~0.5A	5V 0~5A	15V 0~2A	-15V 0~0.5A	5V 0.5~5A	12V 0.2~2.5A	24 0.2~0.5A
纹波及噪音 Wave and noise		50mVp-p	100mVp-p	100mVp-p	100mVp-p	120mVp-p	120mVp-p	100mVp-p	120mVp-p	120mVp-p	80mVp-p	100mVp-p	100mVp-p
进线稳定度 Inlet wire stability		±0.5%	±1%	±0.5%	±0.5%	±1%	±0.5%	±0.5%	±1%	±0.5%	±0.5%	±1%	±1%
负载稳定度 Load stability		±1%	±4%	±1%	±1%	±4%	±4%	±4%	±4%	±1%	±1%	±4%	±1%
效率 Efficiency		72%			72%			72%			72%		
直流电压可调范围 Adjustable range for DC voltage		CH1: ±10%	CH2: ±5%	CH3: ±5%	CH1: ±10%	CH2: ±5%	CH3: ±5%	CH1: ±10%	CH2: ±5%	CH3: ±5%	CH1: ±10%	CH2: ±5%	CH3: ±5%
输入电压范围 Input voltage range		85 ~ 264VAC 120 ~ 370VDC 47 ~ 63Hz											
冲击电流 Impact current		冷启动电流 Cold start current 30A/115VAC 60A/230VAC											
过载保护 Overload protection		105% ~ 150%切断输出，自动恢复 105% ~ 150% cut off the output, automatic recovery											
过电压保护 Over voltage protection		CH1: 115 ~ 135%关闭输出，电源重启后可恢复输出 CH1: 115 ~ 135% shut down O/P voltage, re-power on to recover											
启动、上升、保持时间 Setup, rise, hold up time		300ms, 50ms, 80ms/230VAC 满负载 at full load											
耐压性 Withstand voltage		输入输出间: 1.5kV 输入与外壳间: 1.5kV 输出与外壳间: 0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute											
隔离电阻 Isolation resistance		输入输出间 输入与外壳间 输出与外壳间: 500VDC/100MΩ I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ											
工作温度 Working temperature		-10°C ~ +50°C											
尺寸 Dimension		159 × 98 × 38mm											
重量 Weight		0.55kg											
包装 Packing		34 × 32 × 24CM/30PCS/16.5kg											

### 外形尺寸 Overall dimension(mm)

