

Model	SC-350-12		SC-350-24	
DC voltage	CH1: 13.8V	CH1: 13.4V	CH1: 27.6V	CH2: 26.5V
Rated current	21A	5A	9A	5A
Current range	0~21A	0~5A	0~9A	0~5A
Rated power	358W		386W	
Ripple and noise	150mvp-p		150mvp-p	
DC voltage ADJ.range	±10%, based on different battery charging requirements			
Output Accuracy	±5%		±5%	
Line Regulation	±0.5%	±1%	±0.5%	±1%
Load Regulation	±0.5%	±4%	±0.5%	±4%
Efficiency	82%		85%	
Input voltage range	88~132VAC/176~264VAC(selected by switch)			
Frequency	47~63HZ			
Input AC current	6A/115VAC, 3A/230VAC			
Inrush current	Cold-start current 40A/230VAC			
Leakage current	<0.5mA/240VAC			
Over load protection	Rated output power 105%~150% start over load protection			
	Protection type: AC charging mode, hiccup mode, auto-recovery after fault condition is removed			
Working temp,humidity	-20C~+50°C,20%~90%RH			
Storage temp,humidity	-20°C~+85°C, 10%~90%RH Non-condensing			
Withstand voltage	I/P-O/P: 1.5KVAC: I/P-FG: 1.5KVAC: O/P-FG: 0.5KVAC			
Isolation resistance	I/P-O/P: I/P-FG: O/P-FG: 100M ohms/500VDC			
Demension	215*115*50mm (L*W*H)			
Weight/Packing	1.0kg/20pcs			