

36W POWER ADAPTER

Features:

- . Low Ripple/Noise
- . 2 Years warranty
- . AC to DC power adapter
- . 100% full load burn-in test
- . Plug in / Wall mount type, with US/EU//AU/UK/KC pin
- . Protection: Short circuit/Overload /Over Voltage/Over Temperature



| Model | | WH-36-12 | WH-36-15 |
|-----------------------|----------------------------------|--|----------|
| Output | DC output voltage | 12V | 15V |
| | Output voltage tolerance | +1% | +1% |
| | Rated output current | 3A | 2A |
| | Output current range | 0~ 3A | 0~ 2A |
| | output power | 36W | 30W |
| | Ripple and noise | 100mVp-p | 100mVp-p |
| | DC voltage adjustable range | +10% | +10% |
| | Start, rise, hold time | 200ms,50ms,20ms/230VAC | |
| Input | Input voltage range | 170~264VAC 47~63Hz, 235~373VDC | |
| | AC input current | 0.35A/230VAC | |
| | efficiency | 78% | 78% |
| | Impulse current | Cold start current 30A / 230VAC | |
| | Leakage current | <0.5mA/240VAC | |
| Protection | overload protection | 110% - 135% of rated output power start overload protection | |
| | | Protection mode: fold type current limit, automatic recovery after removal of abnormal load conditions | |
| Environmental Science | Working temperature and humidity | -10 °C ~ + 60 °C ; 20% ~ 90% RH (please refer to load derate curve) | |
| | Storage temperature and humidity | -20 °C ~ + 85 °C ; 10% ~ 95% RH non condensing | |
| | Seismic resistance | 10~ 500Hz, 2G 10min. / 1 cycle, duration 60min, each axis | |
| Security | Pressure resistance | Input output room: 1.5kVac input and ground: 1.5kVac output and ground: 0.5kvac | |
| | insulation resistance | Input output room: input and ground, output and ground: 100M ohms / 500VDC | |
| Other | weight | 0.140kg & apos; 93.5*43.5*33 (L*W*H) | |
| | Packing | 100pcs | |

AC:

American



Chinese



European



British



Australian



DC:

2.5*0.7mm



3.5*1.35mm



4.0*1.7mm



5.5*2.1mm



5.5*2.5mm



MIC

