



60W POWER ADAPTER



Features:

- . Low Ripple/Noise
- . 2 Years warranty
- . AC to DC power adapter
- . 100% full load burn-in test
- . Plug in / Wall mount type, with US/EU/AU/UK/KC pin
- . Protection: Short circuit/Overload /Over Voltage/Over Temperature

Model		WH-60-12	WH-60-24
Output	DC output voltage	12V	24V
	Output voltage tolerance	+1%	+1%
	Rated output current	5A	2.5A
	Output current range	0~ 5A	0~ 2.5A
	output power	60W	60W
	Ripple and noise	50mVp-p	50mVp-p
	DC voltage adjustable range	+10%	+10%
	Start, rise, hold time	200ms,50ms,20ms/230VAC	
Input	Input voltage range	170~264VAC 47~63Hz, 235~373VDC	
	AC input current	0.35A/230VAC	
	efficiency	78%	78%
	Impulse current	Cold start current 30A / 230VAC	
	Leakage current	<0.5mA/240VAC	
Protection	overload protection	110% - 135% of rated output power start overload protection	
		Protection mode: fold type current limit, automatic recovery after removal of abnormal load conditions	
Environmental Science	Working temperature and humidity	-10 °C ~ + 60 °C; 20% ~ 90% RH (please refer to load derate curve)	
	Storage temperature and humidity	-20 °C ~ + 85 °C; 10% ~ 95% RH non condensing	
	Seismic resistance	10~ 500Hz, 2G 10min. / 1 cycle, duration 60min, each axis	
Security	Pressure resistance	Input output room: 1.5kVac input and ground: 1.5kVac output and ground: 0.5kvac	
	insulation resistance	Input output room: input and ground, output and ground: 100M ohms / 500VDC	
Other	weight	0.230kg ×118*53*34 (L*W*H)	
	Packing	50pcs	

