



HDR-100W Din Rail Switching Power Supply



Features:

- . Small volume, low weight, high efficiency
- Protections: Short circuit / Overload
- . Indicator for power on/charge/normal(LED)
- . 100% full load burn-in test
- . Battery protection at low voltage
- . 2 Years warranty

Model	HDR-100-12	HDR-100-15	HDR-100-24	HDR-100-48
DC output voltage	12V 0~7.5A	15V 0~6.6A	24V 0~4.16A	48V 0~2A
Wave and noise	120mVp-p	120mVp-p	150mVp-p	200mVp-p
Inlet wire stability	±1%	±1%	±1%	±1%
Load stability	±1.5%	±1%	±1%	±1%
Efficiency	85%	86%	88%	88%
Adjustable range for DC voltage	±1%	±1%	±1%	±1%
Input voltage range	85~264VAC 120~370VDC 47~63Hz			
Impact current	Cold start current 30A/115VAC 60A/230VAC			
Overload protection	105% -160% cut off the output, automatic recovery			
Other protection	Overcurrent protection / Short-circuit protection			
Setup, rise, hold up time	3000ms, 50ms/230VAC at full load		3000ms, 50ms/115VAC at full load	
Withstand voltage	I/P-O/P: 1.5kV			
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ			
Working temperature	-10℃~+50℃			
Dimension	70x90x54.5mm			
Weight	0.27kg			
Packing				

外形尺寸 Overall dimension(mm)

